

RC3000 Breather fabric

Item number: 02451 00001



Technical data

Description The **breather fabric RC3000** is ideally suited to aerospace applications.

Features

- Non-woven polyester felt capable of operating at temperatures up to 204 °C (400 °F) and pressures up to 13.8 bar (200PSI).
- Will not trap off as many other 680 g/m² (20oz/yd²) breathers will during normal cure cycles.
- Non-toxic, non-corrosive, non-dusting and non- allergenic.
- An excellent breather choice for complex contour, double curvature details due to its multi-directional stretch and low density, high loft construction.
- Ideally suited for use as an edge breather

Product	Breather fabric RC3000	Width: 1,52 m	Roll length: 50 lin m
----------------	------------------------	---------------	-----------------------

Properties	Characteristics
Maximum use temperature	204 °C
Colour	White
Fibre	Polyester
Weight	680 gsm/m ²

RC3000 has no release characteristics and should be separated from the laminate by a suitable porous release fabric or film when used in conjunction with uncured materials.

Storage condition: No special storage conditions required.

Health & safety: No skin irritation problems experienced.

Handling of these products must conform to individual company guidelines and health and safety regulations.

The values presented in this data sheet are typical values and are not to be interpreted as product specifications.
The purchaser is not released from the obligation to inspect the incoming goods. Test findings do not indicate the suitability of the product for a concrete application.