

## LTS90 G Sealant Tape

Item number: 02601 00017



## Technical data

**Description** The **sealant tape LTS90** is ideally suited for de-bulk and medium temperature applications, such as wind energy, marine and glass laminating.

### Features

- Specially formulated with a cost optimised design suitable for ambient, debulk and medium temperature applications.
- Widely used in the wind, marine and glass industries.
- Excellent tack
- Also suitable for high temperature envelope bagging applications.
- Material compatible with most substrates (incl. composite tools) and film materials.
- For optimum results, tape must be allowed to cool to an ambient temperature before stripping from mould surfaces.

<b>Product</b>	Thickness: 3 mm	Width: 12 mm	Roll length: 15 m
----------------	-----------------	--------------	-------------------

Properties	Characteristics
Maximum use temperature	Bag to tool: 150 °C Bag to bag: 180 °C
Colour	Grey <i>Product variant: Black (LTS90 B)</i>
Roll size	15 m x 12 mm x 3 mm
Standard box contents	22 rolls/box
Shelf life	24 month from date of manufacture

**Storage condition:** Temperature: between 5°C and 27°C (41°F and 77°F)  
Must be stored flat in its original containers.  
Boxes should be stacked no more than 5 high.

The values presented in this data sheet are typical values and are not to be interpreted as product specifications. The purchaser is not released from the obligation to inspect the incoming goods. Findings do not indicate the suitability of the product for a concrete application.