

## 606 Flow media

Item number: 02201 00014



## Technical data

**Description** **Flow media 606** is a special knitted mesh that is used for resin distribution in resin infusion and similar processes.  
It can also be used as a reusable flexible/high stretch breather for vacuum bagging and consolidation.

### Features

- Excellent resin flow
- High flexibility, adaptable for different shapes, corners and contours
- Can be used as external or internal resin flow medium
- Does not leave unsightly indentations
- Use up to 180 °C (*Melt point onset is 230 °C*)
- Can be used with all resin systems

|                |                |               |                        |
|----------------|----------------|---------------|------------------------|
| <b>Product</b> | Flow media 606 | Width: 1,25 m | Roll length: 100 lin m |
|----------------|----------------|---------------|------------------------|

| Properties              | Characteristics                 |
|-------------------------|---------------------------------|
| Maximum use temperature | 180 °C                          |
| Colour                  | Clear (cristal)                 |
| Fibre                   | PET polyester monofilament yarn |
| Construction            | Knitted net                     |
| Weight                  | 95 gms/m <sup>2</sup>           |

**NOTE:** *Flow rate of the resin in the mesh roll direction is about 18% faster compared to the resin flow at 90 ° to the mesh roll direction. Therefore take note of the mesh direction when using.*

**Ideal storage condition:** No special storage conditions required.

The values presented in this data sheet are typical values and are not to be interpreted as product specifications.  
The purchaser is not released from the obligation to inspect the incoming goods. Test findings do not indicate the suitability of the product for a concrete application.