

200 G Vacuum foil

Item number: 02602 00035



Technical data

Description The **vacuum foil 200 G** is a green coloured, flexible and high strength coextruded mononylon vacuum bagging film, for oven and autoclave high temperature curing processes up to 200 °C.

This product is not suitable for contact with phenolic resins.

Maximum use temperature: 200 °C

Note: The product can be recycled, UE recycling class PA - 07

Product	Thickness: 50 µm	Width: 1,83 m	Roll length: 250 lin m
Properties	Characteristics		Test Method
Tensile Strength at break	Transverse direction	105 MPa	ASTM D882
	Machine direction	110 MPa	
Elongation at break	Transverse direction	390 %	ASTM D882
	Machine direction	360 %	
Density	1,13 g/cm ³		

Storage condition

Store in original packaging at standard warehouse conditions. ambient temperature between +5 °C and +40 °C ,relative humidity RH between 25 % and 60 %, covered area protected from direct sunlight and UV light/radiation sources.

The above values are only reference values. For specific information on the film's suitability for use in a particular application, please contact COMPOSYST GmbH technical support team for advice.

The values presented in this data sheet are typical values and are not to be interpreted as product specifications. The purchaser is not released from the obligation to inspect the incoming goods. Test findings do not indicate the suitability of the product for a concrete application.