

## 200G Tube Vacuum foil

Item number: 02602 00071



## Technical data

Description

**200G Tube** is a flexible, high strength mononylon vacuum bagging film in green colour suitable for oven and autoclave cure temperatures up to 200°C.

Maximum use temperature: 200°C

The vacuum foil 200G Tube is available as:

> Thickness 50  $\mu$ m & 75  $\mu$ m

> Size 50  $\mu$ m: Available from 25 mm tubular to 2.300 mm tubular /

4.600 mm V-sheet

75  $\mu m$ : Available up to 2.000 mm tubular / 4.000 mm V-sheet

Product	Thickness:	50 μm	Width:	0,90 m	Roll length: 250 lin m
Properties		Characteristics			Test Method
Density			1,13 g/m³		internal
Production width		tubular	up to 2,30 m	-0/+2 %	internal
Thickness			50 μm	±10 %	ISO 4593
Tensile Strength at b	oreak	TD*:	330 N/mm <sup>2</sup>	±15 %	ASTM D882
Elongation at break		TD*:	340 %	±15 %	ASTM D882
Colour		Green			

Note: The above values are to be understood as reference only.

For any additional advice on the film's suitablilty in specific applications contact COMPOSYST GmbH technical

department.

\*) TD: Transverse direction

Storage: To be stored in original packaging only.

The values presented in this data sheet are typical values and are not to be interpreted as product specifications.

The purchaser is not released from the obligation to inspect the incoming goods. Test findings do not indicate the suitability of the product for a concrete application.

COMPOSYST GmbH Am Penzinger Feld 15b D-86899 Landsberg am Lech Germany Phone: Fax: E-mail: Web: +49 (0) 8191 96363-0 +49 (0) 8191 96363-99 office@composyst.com www.composyst.com

Status 01/2023

© 2020 COMPOSYST GmbH

