

## Vacuum Breach Unit

Item number: 02900 00067







## Technical data

Description

Vacuum Connectors — also referred to as **vacuum breach units** (VBUs) or vacuum valves, provide a vacuum connection through the vacuum bagging film. This two-part, through-bag connector has a 50mm diameter base and male  $\frac{1}{4}$ " BSPP thread

## **Features and Benefits**

- Allows air evacuation from the vacuum bag.
- · Can be used in oven and autoclave.
- 1/4" BSP thread compatible with brass or steel non-return plug or socket.
- Silicone gasket can be replaced if needed.
- Two piece VBUs are self-perforating, removing the need to cut a hole in the bagging film.
- · Long service life.

Use with temperatures up to 260 °C / 500 °F.

Materials	Connector: Light weight aluminium Gasket: Silicone
Base Plate Diameter:	50 mm - round Height: 37 mm
Screw Thread:	1/4 " - male
Max. temperature	Gasket red: 260 °C Gasket grey: 210 °C
Further details	Gasket red: Ø 53 mm, thickness: 3,0 mm  Gasket grey: Ø 47 mm, thickness: 1,2 mm  > Both gaskets are included in the scope of supply.
Storage: No specific requirement.	

The values presented in this data sheet are typical values and are not to be interpreted as product specifications.

The purchaser is not released from the obligation to inspect the incoming goods. Findings do not indicate the suitability of the product for a concrete application.

COMPOSYST GmbH Am Penzinger Feld 15b D-86899 Landsberg am Lech Germany

Health &

Safety:

Phone: +49 (0) 8191 96363-0 Fax: +49 (0) 8191 96363-99 E-mail: office@composyst.com Web: www.composyst.com

Please refer to the product MSDS for safe handling, personal protective

equipment recommendations and disposal considerations.

Status 11/2024

© 2020 COMPOSYST GmbH

